

Overview fire protection

	Properties	DIN 5510 / Part 2	Smoke toxicity DIN 5510-2 attachment C	NFF 16 101	BS 6853 Table 7	UNE 23-723	Bombardier SMP 800-C	UNI CEI 11170	EN 45545-2+A1:2016	NFPA130 ASTM C1166, ASTM E662,
1746-022	EPDM, black 60 +/- 5 ShA	expired	expired	/	/	/	/	/	/	/
1747-032	EPDM, black 70 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
0505-791	EPDM, RAL 7035, light-grey 65 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
0505-789	EPDM, Sikkens 65 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
0505-787	EPDM, Mankiewicz, ochre 65 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
0505-784	EPDM, RAL 7012, basalt-grey 65 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
9704-812 NEW	EPDM, RAL 7005, mouse-grey 65 +/- 5 ShA	S4 SR2 ST2	yes	/	/	/	/	/	/	/
T 9616	EPDM, black 70 +/- 5 ShA	expired	expired	expired	expired	/	/	/	HL 3	/
T 9608	EPDM, black 60 +/- 5 ShA	/	/	expired	expired	expired	/	expired	HL 3	/
HF 45-2500	EPDM, black 50 +/- 5 ShA	/	/	/	/	/	/	/	HL 3	/
HF 45-1611 NEW	EPDM, RAL7035, light-grey 50 +/- 5 ShA	/	/	/	/	/	/	/	HL 3	/
HF 45-1000	EPDM, black 60 +/- 5 ShA	expired	expired	yes	/	/	yes	/	HL 3	yes
HF 45-2200	EPDM, black 60 +/- 5 ShA	/	/	/	/	/	/	/	HL 2	yes
HF 45-1700	EPDM, black 70 +/- 5 ShA	/	/	/	/	/	/	/	HL 3	/